










Equipment Specifications

		FS050 FS150		FS200 FS209		SPS8 SPS8D		SPS10 EZOFF		FS351		LNX8 X1 X3			
Drum Rotation Power Options	Cutter Rotation (Down, Up, Rotary)	D	R	D	D	D	D	D	U	D		R	R	R	
	Electric (E), Air (A), Hydraulic (H)	EA	EA	E	E	E	E	E		E		E	H	H	
	Gasoline (G), Propane (P)			G	G	G	G	G		GP		G		GP	
Cutter Drum/tool choices	Erase-it (24, 48, 72 carbide pins) 											•	•	•	
	Shave/Groove-it (diamond packs) 								•	•					
	Plane-it (carbide picks) 								•	•		•	•	•	
	Strip-it (4N1 full-width carbide) 	•		•	•	•	•	•	•	•					
	Flail-it (carbide flails) 	•	•	•	•	•	•	•	•	•					
	Mill-it (carbide millers) 	•	•	•	•	•	•	•	•	•					
	Scrape-it (carbide scrapers) 	•	•	•	•	•	•	•	•	•					
	Finish-it (beam or stars) 	•	•	•	•	•	•	•	•	•					
	Cure-it (wire brush packs) 	•	•	•	•	•	•	•	•	•			•	•	•
Standard Specifications and Available equipment options	Removal width/pass (≤ inches) ^(^ swivel engaged)	2	7	8	8	8	8	10	10	16		8	8	20	
	Removal depth/pass (≤ inches)	1/16	1/16	1/8	1/8	1/8	1/8	1/4	1/4	3/8		1/8	1/8	1/8	
	Hourly Production rate (SF) (approx.)	100	100	400	400	500	500	700	1500	1000		800	1000	2400	
	Height (inches)	9	11	39	39	44	44	44	48	48		40	24	40	
	Width (inches)	8	12	14	14	19	19	19	34	26		31	18	46	
	Length (inches)	19	20	42	42	38	38	38	85	44		47	27	60	
	Weight (lbs) (without drum, attachments)	12	15	125	150	225	225	250	450	790		450	480	680	
	•Variable depth adj + Engage cam lever (○)			●	●	●	●	●	●	●		●	•	•	
	Cut distance to wall (in inches)	.25		.60		1.25		6		4		8	6	6	
	•Pressure controls + Weight plates (○)											●	•	•	
	Vacuum Port w/Containment shroud	•	•	•	•	•	•	•	•	•		•	•	•	
	Cutter shaft OD (● Bushed drums)	10 mm	10 mm	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	25 mm		•	•	•	
	Qty wheels + Feathering caster (○)			③	③	4	④	④	④	3 of 4		④	④	④	
	•Optional water controls Tank (○)			•	•	●	●	●	●	●		●	●	●	
	Remote power shut-off			•	•	•	•	•	•	•		•	•	•	
	Vibration Dampening Handlebar	•	•	•	•		•	•	•	•		•			
	Easy Drum Access (S-sideplate, L-lift unit)	S	L	S	S	L	S	S	S	S		L	L	L	
	Direct (D) or Belt-drive (B) system	D	D	B	B	B	B	B	B	B		B	D	B	
	Bearings Sealed(1) or Serviceable(2)	1	1	1	1	2	1	1	1	1		1	1	1	
	Parking Brake—Standard vs. Optional					O	O	O	O	O		S			
	Manual, Self-Propelled, Ride-on	M	M	M	M	M	M	M	R	S		M	R	R	