

Hazardous Dust Protection



Dust-Control Solution



Always operate any dust-producing equipment with an approved filter dust containment system



Order Number	Power
MV360	110V 50/60Hz, 2 motors, 2400W/20A
Airflow	208 CFM @ 98" waterlift
Weight	62 lbs (28 kg)
Dimensions	16"x16"x28" (w/o separator) (41 cm x 41 cm x 71 cm)
FILTER	Polyester + PTFE, ~1000 hrs life with separator (500 w/o)
Optional	MV-SA and MVSC cyclone separators

MV360™ Performance Benefits:

MV360 (110v), MV1000 (220V), and MV5500 (gas) are compact, portable, industrial-grade vacuum systems, with optional MV-SA or SC cyclone separator (required purchase) for best use with portable concrete and asphalt grinding and cutting machines.

- Non-clogging automatic self-cleaning shakedown for continuous use
- All-steel construction w/industrial safety yellow powder coat (no plastic)
- 2 electric motors, 2 HP total, use one or both motors, depending on power needs
- Heavy-duty steel frame with industrial non-marking casters
- Upright quick-dump collection canister
- Tested and ready to work

Included Accessories:

- (1) collection hose, 2"x33' (50 mm x 10m), (1) separator/vac connection hose, (2) clamps, (1) velcro collection bag strap belt, (1) 3" (76mm) connector, (1) separator/vac connection bracket, (1) elbow pipe connector, (1) floor nozzle, floor wand, round brush, floor brush, Y-connector, (4) 2" (50mm) connectors

Optional:

- Cyclone pre-separator

SMITHmfg.com

