

Erase-Remove-Prep



Erase Markings Without Water, Grooving, or Ghost Lines



Erase it



169068.3000



169068.3001



169068.3002

Plane it



X3.00.120.66A

Cure it



X3.00.101A



Order Number	Power
X1.G20	Low-flow hydraulic (≥13 gal/min 2,500 PSI)
X1.G40	Hi-flow hydraulic (≥27 gal/min 3,000 PSI)
Removal Cut Width	≤ 8" pp (20cm)
Weight	480 lbs (217 kg) w/o cutters
Dimensions	27" L x 18" W x 24" H (68 cm x 46 cm x 61 cm)
Optional	Cutter drum assemblies

SMITHmfg.com

X1™ Performance Benefits:

Single spindle, low profile design for effective rotary erasing performance. Permanently remove markings without water, grooves, ghost lines, or undermining of the road. The X1 leaves an ideal surface finish without micro-cracking at less cost than water-blasting.

- All-steel unitized heavy-duty construction with material-containment shroud
 - For use with high- or low-flow skidloaders
 - Manually adjustable (spring-tensioned) height and pitch control
 - Terrain-following suspension floating cutting tool design promotes bevel edges
 - Dust and debris shroud with dual vacuum dust-collection ports
 - Bobtach skid-loader mounting bracket with manual side-shift
- Optional:**
- Variety of cutters to remove all markings or surface prep on concrete or asphalt
 - HEPA gas-powered vacuum system with cyclone separator
 - Dual-camera video guidance system

